



I'm not a robot



Continue

# Halfords rear cycle carrier fitting instructions model number chart pdf

Locking system to hold cycle wheels in place. • Ensure that the vehicle boot lid/rear bumper are free from dirt and grime. When not in use this bike rack folds flat for space saving storage. Straps should be checked routinely for signs of wear and abrasion, and any worn straps must be replaced immediately. After driving for a few miles STOP and check that all straps are secure and tight. Extra care should be taken when negotiating rough road surfaces, humps and ferry ramps. All lengths are approximate. Kit Contents Panel hookChassis hookDumbbells160cm95cm Main frame Please follow instructions carefully to ensure the safety of yourself and other road users. The initial assembly and fitting of the carrier will take approximately 15 minutes. Before you begin: • Due to the construction of boot lids we recommend only two cycles be carried on saloon cars with this carrier. • Make sure all parts are included in the package. • Ensure that the vehicle boot lid/rear bumper are free from dirt and grime. High Mount 3 Bike Carrier Fitting Instructions Made in the UK Halfords Ltd, Washford Redditch, B98 0DE PI386-02 halfords hi 3 bike 1/2/10 15:13 Page 1 Avoid any vehicle bodywork of insufficient strength, trim and items such as aerofoils or spoilers. IMPORTANT! Carrier straps must always be re-tightened after cycles have been mounted to the carrier. Extra care should be taken when negotiating rough road surfaces, humps and ferry ramps. All lengths are approximate. 95cm Please follow instructions carefully to ensure the safety of yourself and other road users. The initial assembly and fitting of the carrier will take approximately 15 minutes. Before you begin: • Due to the construction of boot lids we recommend only two cycles be carried on saloon cars with this carrier. • Make sure all parts are included in the package. • Ensure that the vehicle boot lid/rear bumper are free from dirt and grime. halfords hi 3 bike 1/2/10 15:13 Page 1 The initial assembly and fitting of this carrier will take approximately 15 minutes. Kit Contents REFER TO THE SEPARATE APPLICATION GUIDE TO DETERMINE THE CORRECT FITTING KIT. x2 x2 x2 Carries 3 Bikes. Product may differ from images shown. Special Recommendations Avoid any vehicle bodywork of insufficient strength, trim and items such as aerofoils or spoilers. IMPORTANT! Carrier straps must always be re-tightened after cycles have been mounted to the carrier. If in any doubt ask in store. New easy fit individual cycle holders, with anti-scratch rubber inserts. Please Note: When carrying a 'step through' or children's bike, you will need to purchase the Halford False Cross Bar in order to properly mount your bike onto the bike rack. 45kg max load weight, max 15kg per bicycle (not suitable for electric bikes). DO NOT operate the wiper with the carrier fitted. When positioning cycles on the carrier ensure that they do not project beyond the profile of the vehicle and that no part of any cycle can touch the paintwork. The use of rear mounted cycle carriers may be restricted in certain countries outside the UK. Always check with the relevant national tourist authorities prior to commencing your journey. Use cloth or foam padding to prevent abrasion damage occurring between the frames of your cycles, or from contact between the cycles and the cycle carrier. Care must be taken when positioning and loading the cycle carrier to avoid placing cycle tyres near the exhaust, and to ensure that a satisfactory ground clearance is maintained between the cycles and the road. Halfords hi 3 bike instructions 6/8/07 12:01 PM Page 1 Made in the UK Halfords Ltd, Washford Redditch, B98 0DE PI480-01 Metal Clamp High 3 Bike Carrier Fitting Instructions Please follow instructions carefully to ensure the safety of yourself and other road users. If necessary, tighten the straps and tidy away any loose ends. This must be repeated at suitable intervals depending on the nature of the road. Do not exceed 45kg maximum load (3 adult cycles) or 30kg maximum load (2 adult cycles) when the carrier is used on a booted saloon. To ensure full compliance with the road traffic regulations, the use of lighting board/numberplate is required if your vehicle's existing lighting/number plates are obscured by the use of the carrier. Drive with care, the handling characteristics of your vehicle will be affected when carrying cycles, (e.g. cornering, braking, side winds etc.). Retain these instructions for future reference, ensure that any other users of the cycle carrier are familiar with their contents. The carrier may obstruct the rear window wiper of your vehicle. Before you begin: • Under no circumstances should this carrier be fitted to your car unless it is adjusted to the exact settings specified in the enclosed vehicle application list. Not compatible with your vehicle if the vehicle has a boot spoiler. Comes part assembled - assembly and fitting time just 15 minutes. Side straps for extra stability. • Due to the construction of boot lids we recommend only two cycles be carried on saloon cars with this carrier. • Make sure all parts are included in the package. This carrier must not be fitted to any vehicle not listed.



o  
i  
  
o  
  
u